



中国国家强制性产品认证证书

证书编号：2024011002652057

认证委托人名称及地址

威森电子（珠海）有限公司
珠海市金湾区三灶镇阳春路3号

生产者名称及地址

威森电子（珠海）有限公司
珠海市金湾区三灶镇阳春路3号

生产企业名称及地址

威森电子（珠海）有限公司
广东省珠海市金湾区三灶镇阳春路3号

产品名称和系列、型号、规格

LED 模块用交流电子控制装置（LED 控制装置，独立式，恒流模式，安全特低电压，不可调光， $t_a:50^{\circ}\text{C}$ ， $t_c:85^{\circ}\text{C}$ ，II 类，IP20，适宜直接安装在普通可燃材料表面，定温热保护： 110°C ）
见附页。220-240V~ 50/60Hz

产品标准和技术要求

GB 17625.1-2022; GB/T 17743-2021; GB 19510.1-2009; GB 19510.14-2009

上述产品符合《强制性产品认证实施规则 照明电器》（CNCA-C10-01:2014）的要求，特发此证。

发证日期：2024 年 08 月 13 日 有效期至：2029 年 07 月 02 日

本证书为变更证书，证书首次颁发日期：2024 年 07 月 03 日
证书信息和有效性可扫描下方二维码或登录发证机构网站查验，
也可在认监委网站（www.cnca.gov.cn）查询。

经中国合格评定国家认可委员会认可 CNAS C001-P



签发：

谢肇煦



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

中国质量认证中心有限公司





中国国家强制性产品认证证书

证书编号：2024011002652057

证书附页：第 1 页 共 1 页

序号	型号	输入电流 (mA)	输出电流(mA)	输出电压 (Vdc)	最大输出 电 压 (Vdc)	输出功率 (W)
1	G5S20W500 LR-Z	Max.130mA	500mA (恒流)	30-42Vdc	53Vdc	15-21W
2	G5S15W105 0LR-Z	Max.95mA	1050mA (恒流)	9-15Vdc	26Vdc	9.5-15.5W
3	G5S15W700 LR-Z	Max.85mA	700mA (恒流)	13-21Vdc	32Vdc	9-14.5W
4	G5S15W500 LR-Z	Max.85mA	500mA (恒流)	18-30Vdc	42Vdc	9-15W
5	G5S15W350 LR-Z	Max.85mA	350mA (恒流)	26-42Vdc	53Vdc	9-14.5W
6	G5S15W300 LR-Z	Max.75mA	300mA (恒流)	26-42Vdc	53Vdc	8-12.5W
以上型号输入：220-240V~50/60Hz						

本页为证书附页，应与证书主页同时使用。



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

中国质量认证中心有限公司



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE NO.: 2024011002652057

NAME AND ADDRESS OF THE APPLICANT

WEISEN ELECTRONIC (ZHUHAI) CO.,LTD.

No.3, YangChun Road, Sanzao Town, Jinwan District, Zhuhai City , Guangdong Province, China

NAME AND ADDRESS OF THE MANUFACTURER

WEISEN ELECTRONIC (ZHUHAI) CO.,LTD.

No.3, YangChun Road, Sanzao Town, Jinwan District, Zhuhai City , Guangdong Province, China

NAME AND LOCATION OF THE FACTORY

WEISEN ELECTRONIC (ZHUHAI) CO.,LTD.

No.3, YangChun Road, Sanzao Town, Jinwan District, Zhuhai City , Guangdong Province, China

PRODUCT NAME,MODEL AND SPECIFICATION

A.C. Supplied Electronic Controlgear For LED Modules (Independent, Constant Current Mode, SELV,
ta:50℃, tc:85℃, Class II , IP20, Suitable For Direct Mounting On Normally Flammable Material,
Temperature Declared Thermally Protected:110℃)

See Appendix. 220-240V ~ 50/60Hz

STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB 17625.1-2022;GB/T 17743-2021;GB 19510.1-2009;GB 19510.14-2009

This is to certify that the above mentioned product(s) complies with the requirements of
implementation rules for compulsory certification(REFNO. CNCA-C10-01:2014).

Valid from: Aug.13,2024

Valid until: Jul.02,2029

Date of original issued: Jul.03,2024

The certificate information and validity could be checked by scanning the QR code below or logging in to
the website of the issuing authority, or on the website of the CNCA (www.cnca.gov.cn).

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P



SIGNATURE:

谢肇煦



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.





CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. :2024011002652057

Appendix: Page 1 of 1

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

序号	型号	输入电流 (mA)	输出电流(mA)	输出电压 (Vdc)	最大输出 电 压 (Vdc)	输出功率 (W)
1	G5S20W500 LR-Z	Max.130mA	500mA (恒流)	30-42Vdc	53Vdc	15-21W
2	G5S15W105 0LR-Z	Max.95mA	1050mA (恒流)	9-15Vdc	26Vdc	9.5-15.5W
3	G5S15W700 LR-Z	Max.85mA	700mA (恒流)	13-21Vdc	32Vdc	9-14.5W
4	G5S15W500 LR-Z	Max.85mA	500mA (恒流)	18-30Vdc	42Vdc	9-15W
5	G5S15W350 LR-Z	Max.85mA	350mA (恒流)	26-42Vdc	53Vdc	9-14.5W
6	G5S15W300 LR-Z	Max.75mA	300mA (恒流)	26-42Vdc	53Vdc	8-12.5W
以上型号输入: 220-240V~50/60Hz						

This page is attached to the certificate and should be used at the same time as the certificate page.



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.