

# CERTIFICATE

Issued to:  
Applicant:  
**HEP Tech Co., Ltd.**  
No. 20, Jingke 7th Rd., Nantun Dist.,  
40852 Taichung City, Taiwan

Licensee:  
**HEP GmbH**  
Ramsloh 10  
58579 Schalksmühle, Germany

Product : Current controlled LED Driver  
Trade name(s) : HEP GROUP®  
Type(s)/model(s) : LNDC15W700NLRP-T2CH

The product and any acceptable variation thereto as specified in the Annex to this certificate and the documents therein referred to.

DEKRA hereby declares that the above-mentioned product has been certified on the basis of:

- a type test according to EN 61347-1:2015, EN 61347-1:2015/A1:2021, EN 61347-2-13:2014, EN 61347-2-13:2014/A1:2017 and EN IEC 62384:2020
- an inspection of the factory location according to CENELEC Operational Document CIG 021
- a DEKRA certification agreement with the number 2013493


DEKRA hereby grants the right to use the ENEC certification mark.

The ENEC certification mark may be applied to the product as specified in this certificate for the duration and under the conditions of the ENEC certification agreement.

This certificate is issued on 31 January 2024 and expires upon withdrawal of one of the above mentioned standards.

Certificate number: 88-133853

DEKRA Certification B.V.



B.T.M. Holtus  
Managing Director



Miranda Zhou  
Certification Manager

© Integral publication of this certificate is allowed

ACCREDITED BY THE  
DUTCH ACCREDITATION  
COUNCIL



**SPECIFICATION OF THE CERTIFIED PRODUCT****Product data**

Product	: Current controlled LED Driver
Trade name(s)	: HEP GROUP®
Type(s)/model(s)	: LNDC15W700NLRP-T2CH
Rated supply voltage	: 220-240 Vac
Supply frequency	: 50-60 Hz
Rated supply current	: 95 mA
Power factor	: 0,6C-0,95
Rated output current	: 125-700 mA
Rated output power	: 1,9-15 W
Output voltage range	: 15-54 Vdc
Uout	: 60 V
Ambient temperature range (ta)	: -20...+60°C
Max. case temperature (tc)	: 80 °C
Degree of protection	: IP20
Classification of installation	: built-in

**TESTS****Test requirements**

EN 61347-1:2015  
EN 61347-1:2015/A1:2021  
EN 61347-2-13:2014  
EN 61347-2-13:2014/A1:2017  
EN IEC 62384:2020

**Test result**

The test results are laid down in DEKRA test file 343214600.

**Additional information**

The LED controlgear is a built-in SELV controlgear with double or reinforced insulation for LEDs with constant current. The LED controlgear can be used inside of luminaires. The type is potted. It is a DALI-2 (DT8) tunable white dimmable LED Driver and the output current is adjustable by NFC function. The insulation between primary and secondary is SELV and between primary and housing is considered as double insulation. The insulation between DALI and primary circuit is basis insulated and to the secondary circuit is double or reinforced insulation. The controlgear has free lead wires. The max. enclosure temperature under abnormal or fault conditions is 110°C.

The list of components is laid down in test report 3432146.50.

**Conclusion**

The examination proved that all requirements were met.

**Factory locations**

HEP GmbH  
Ramsloh 10  
58579 Schalksmühle, Germany

Weisen Electronic Co. Ltd.  
No. 3 Yangchun Rd., Jinwan Dist.  
519040 Zhuhai City Guangdong, China