

Approval Marks






Item		Value	Remark
Input	Nominal voltage	220–240V	
	Nominal frequency	50/60Hz	
	AC voltage range	198–264V	
	DC voltage range (start)	NA	
	DC voltage range (operation)	NA	
	Nominal current	75mA	Full load @230VAC
	Total Harmonic Distortion (THD)	<15%	Full load @230VAC
	Power factor	0.9C	Full load @230VAC
	Displacement factor	0.9C	Full load @230VAC
	Efficiency	85%(Typ.)	Full load @230VAC
	No-load power	NA	
	Stand-by power	NA	
	Protection class	II	Suitable for class II luminaires
	Inrush current	6 A / 15 μ s	Full load @230VAC
Output	Max.units per circuit breaker	Type B , 10A MCB	53
		Type B , 16A MCB	85
		Type C , 10A MCB	67
		Type C , 16A MCB	107
	Touch current	< 0.7mA peak	IEC/EN 61347-1
	Nominal voltage range	25-40Vdc	
	Maximum voltage	55Vdc	
	Nominal current range	350mA	
	Current accuracy	$\pm$ 5%	
	Typical output LF current ripple	$\pm$ 5%	Full load @230VAC Low Frequency<120Hz
Output	SVM	$\leq$ 0.4	Full load @230VAC
	PstLM	$\leq$ 1	Full load @230VAC
	Starting time	< 0.5 S	Full load @230VAC
	Nominal power range	8.8-14W	
	Maximum power	14W	

	Item	Value	Remark
Environment	Ambient temperature range t_a	-20°C- +45°C	
	Maximum case temperature t_c	75°C	
	Max. case temp. in fault condition	110°C	When operating under fault conditions, the temperature of the enclosure at any location should not exceed 110 °C
	Storage temperature range	-25°C- +80°C	
	Relative humidity	10%-85%	
	Surge transient protection	1kV	L/N
	Environmental rating	Indoor	
	IP rating	IP20	
	Mains switching cycles	> 10,000	
	Expected lifetime	> 50,000 h, t_c 75 °C @ t_a 45 °C > 100000 h, t_c 65 °C @ t_a 35 °C	0.2 % / 1,000 h failure rate 0.1 % / 1,000 h failure rate
Packing	Gross weight/box	11.8 kg	
	Net weight/box	10.6 kg	
	Pcs/box	132 PCS	
	Dimension/box	490(L)*270(W)*225(H)mm	
Protections			
	Short-circuit Protection	Auto recovery	
	Open-circuit Protection	Auto recovery	
	Overload Protection	Auto recovery	
Conformity & Standards			
	Safety standard:	EN 61347-1, EN 61347-2-13, EN62493	
	SAA standard:	AS/NZS 61347.1, AS/NZS IEC 61347.2.13	
	EMC standard:	EN55015, EN61000-3-2, EN61000-3-3, EN61547	
	Performance:	EN62384	
	CCC standard:	GB17625.1,GB/T17743,GB19510.1,GB19510.14	
Cable information			
PRI Connection			
	Cable cross-section	0.75-1.5□/AWG 18-16	
	Stripping	9mm	
	Pull test cable type	H03VV(H2)-F 2x0,75-1,0 mm ² ,H05VV(H2)-F 2x0,75 mm ²	
SEC Connection			
	Cable cross-section	0.5-1.5□/AWG 20-16	
	Stripping	9mm	
Terminal information			
PRI Push button/Angled Entry			
SEC Push button/Angled Entry			


Subject to change without notice, HEP guarantees all products perform functionally well

*If not mentioned, all the test conditions are based on full load at 230VAC input (for 220-240 VAC input).



Physical

Parameter



L : 115 mm W : 41 mm H : 25 mm
M 102.8 mm W1: 31 mm R : 2.1 mm

Slot On One Side Allowing Alignment : M+/-3 mm
Tolerance : +/-1 mm , R : +/-0.5 mm
Housing Material : Polycarbonate
Soldering : Lead-Free, Comply With RoHS
Label : Surface Print

Wiring Diagram

